

Printing date 29.07.2019

Version number 11

Trade name:	Smooth Surface Cleaner	
Article number: 1.2 Relevant identified uses of	87604, 87612, 87613	
the substance or mixture and uses advised against	No further relevant information available.	
Application of the substance / the mixture	Cleaner solvent	
1.3 Details of the supplier of the		
Manufacturer/Supplier:	AKEMI chemisch technische Spezialfabrik GmbH Lechstrasse 28 D 90451 Nürnberg	Tel. +49(0)911-64296 Fax. +49(0)911-64445 e-mail info@akemi.d
Further information obtainable	Laboratory	
1.4 Emergency telephone number:	Product Safety Department AKEMI chemisch technis Tel. +49(0)911-64296-59 Reachable during the following office hours:	che Spezialfabrik GmbH
	Monday – Thursday from 07:30 a.m. to 16:30 p.m. Friday from 07:30 a.m. to 13:30 p.m. +44 (171) 635 91 91	
	National Poison Inform. Centre Medical Toxicology Unit Avalonley Road	
	London SE14 5ER	
SECTION 2: Hazards identificati		
2.1 Classification of the substar	nce or mixture	
2.1 Classification of the substar	nce or mixture	
2.1 Classification of the substar Classification according to Regula GHS02 flame Flam. Liq. 2 H225 Highly fl	nce or mixture tion (EC) No 1272/2008 ammable liquid and vapour.	
2.1 Classification of the substar Classification according to Regula GHS02 flame	nce or mixture tion (EC) No 1272/2008 ammable liquid and vapour.	
2.1 Classification of the substar Classification according to Regula GHS02 flame Flam. Liq. 2 H225 Highly fl	nce or mixture tion (EC) No 1272/2008 ammable liquid and vapour.	
2.1 Classification of the substar Classification according to Regula GHS02 flame Flam. Liq. 2 H225 Highly fl	nce or mixture tion (EC) No 1272/2008 ammable liquid and vapour.	
2.1 Classification of the substar Classification according to Regula GHS02 flame Flam. Liq. 2 H225 Highly fl GHS08 health hazard Asp. Tox. 1 H304 May be GHS09 environment	nce or mixture tion (EC) No 1272/2008 ammable liquid and vapour.	
2.1 Classification of the substar Classification according to Regula GHS02 flame Flam. Liq. 2 H225 Highly fl GHS08 health hazard Asp. Tox. 1 H304 May be GHS09 environment	nce or mixture tion (EC) No 1272/2008 ammable liquid and vapour. fatal if swallowed and enters airways.	
2.1 Classification of the substar Classification according to Regula GHS02 flame Flam. Liq. 2 H225 Highly fl GHS08 health hazard Asp. Tox. 1 H304 May be GHS09 environment Aquatic Chronic 2 H411 Toxic to GHS07 Eye Irrit. 2 H319 Causes	nce or mixture tion (EC) No 1272/2008 ammable liquid and vapour. fatal if swallowed and enters airways.	
2.1 Classification of the substar Classification according to Regula GHS02 flame Flam. Liq. 2 H225 Highly fl GHS08 health hazard Asp. Tox. 1 H304 May be GHS09 environment Aquatic Chronic 2 H411 Toxic to GHS07 Eye Irrit. 2 H319 Causes	ammable liquid and vapour. fatal if swallowed and enters airways. aquatic life with long lasting effects.	

according to 1907/2006/EC, Article 31

Printing date 29.07.2019

Version number 11

Revision: 29.07.2019

Trade name: Smooth Surface Cleaner

		(Contd. of page 1)
Hazard pictograms		
	GHS02 GHS0	7 GHS08 GHS09
· Signal word	Danger	
 Hazard-determining components 		
of labelling:		eum), hydrotreated light
		eum), hydrotreated heavy
	propan-2-ol	en al la Participa de la composición de
Hazard statements		nmable liquid and vapour.
		erious eye irritation. e drowsiness or dizziness.
		al if swallowed and enters airways.
		quatic life with long lasting effects.
 Precautionary statements 	P101	If medical advice is needed, have product container or label
<u>riocautonary etatemente</u>	1 101	at hand.
	P102	Keep out of reach of children.
	P103	Read label before use.
	P210	Keep away from heat, hot surfaces, sparks, open flames and
		other ignition sources. No smoking.
	P243	Take action to prevent static discharges.
	P271	Use only outdoors or in a well-ventilated area.
	P273	Avoid release to the environment.
	P280	Wear protective gloves / eye protection.
	P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/
	Dood	doctor.
	P331	Do NOT induce vomiting.
	P302+P352 P304+P340	IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep
	F304+F340	comfortable for breathing.
	P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes.
	1 00011 00111 0	Remove contact lenses, if present and easy to do. Continue
		rinsing.
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.
	P501	Dispose of contents/container in accordance with local/
		regional/national/international regulations.
 Additional information: 	EUH066 Repeat	ed exposure may cause skin dryness or cracking.
2.3 Other hazards		
Results of PBT and vPvB assess		
• <u>PBT:</u>	Not applicable.	
· <u>vPvB:</u>	Not applicable.	

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture: consisting of the following components.

 Dangerous components: 		
CAS: 68920-06-9	Naphtha (petroleum), hydrotreated light	25-50%
EC number: 920-750-0	Flam. Liq. 2, H225	
Reg.nr.: 01-2119473851-33	Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411 STOT SE 3, H336	
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	12.5-25%
EC number: 919-857-5	📀 Flam. Liq. 3, H226	
Reg.nr.: 01-2119463258-33	🚯 Asp. Tox. 1, H304	
	🚯 STOT SE 3, H336	
		(Contd. on page 3)

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 29.07.2019

Version number 11

Revision: 29.07.2019

Trade name: Smooth Surface Cleaner

	(Co	ontd. of page 2)
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5	ethanol Flam. Liq. 2, H225 Eye Irrit. 2, H319	12.5-25%
Reg.nr.: 01-2119457610-43		
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	12.5-25%
CAS: 109-87-5 EINECS: 203-714-2 Reg.nr.: 01-2119664781-31	dimethoxymethane Flam. Liq. 2, H225	12.5-25%
· Regulation (EC) No 648/2004 on	detergents / Labelling for contents	
aromatic hydrocarbons, aliphatic l	•	≥30%
Additional information:	For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

· 4.1 Description of first aid measures

After inhalation:	Supply fresh air; consult doctor in case of complaints.
	In case of unconsciousness place patient stably in side position for
	transportation.
After skin contact:	Generally the product does not irritate the skin.
	Rinse with warm water.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a
	doctor.
 After swallowing: 	Do not induce vomiting; call for medical help immediately.
• 4.2 Most important symptoms	
and effects, both acute and	
delayed	No further relevant information available.
• 4.3 Indication of any immediate	
medical attention and special	
treatment needed	No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable extinguishing agents: For safety reasons unsuitable water with full jet 5.2 Special hazards arising from the substance or mixture spray or mixture hour relevant information available. 5.3 Advice for firefighters Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

 6.1 Personal precautions, 	
protective equipment and	
emergency procedures	Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions:	Do not allow product to reach sewage system or any water course.
	Inform respective authorities in case of seepage into water course or sewage system.
	Prevent seepage into sewage system, workpits and cellars.
	Do not allow to enter sewers/ surface or ground water.
	(Contd. on page 4)

(Contd. on page 4)

inting date 29.07.2019	Version number 11	Revision: 29.07.201
ade name: Smooth Surface	Cleaner	
6.2 Mothedo and motorial f		(Contd. of page
<u>6.3 Methods and material fe</u> containment and cleaning		nite, acid binders, univers
· 6.4 Reference to other sect	Dispose contaminated material as waste according Ensure adequate ventilation. Do not flush with water or aqueous cleansing agent See Section 7 for information on safe handling. 	S
SECTION 7: Handling and	storage	
· 7.1 Precautions for safe		
handling	Ensure good ventilation/exhaustion at the workplace	е.
	Open and handle receptacle with care. Prevent formation of aerosols.	
 Information about fire - and 	Frevent formation of aerosols.	
explosion protection:	Keep ignition sources away - Do not smoke. Protect against electrostatic charges.	
	rage, including any incompatibilities	
 Storage: Requirements to be met by 		
storerooms and receptacles:	Store in a cool location.	
	Observe official regulations on storing packagings v	with pressurised containers.
 Information about storage in common storage facility: 	one Store away from foodstuffs.	
• Further information about sto		
conditions:	Protect from frost.	
	Keep container tightly sealed. Do not seal receptacle gas tight.	
	Store in cool, dry conditions in well sealed receptac	les.
	Protect from heat and direct sunlight.	
• <u>Storage class:</u>	3 No further relevent information available	
7.3 Specific end use(s)	No further relevant information available.	
SECTION 8: Exposure cont		
• Additional information about design of technical facilities:	No further data; see item 7.	
· 8.1 Control parameters	that require monitoring at the workplace:	
. Incredients with limit values t	that require mentioning at the workplace.	
Ingredients with limit values 1 64-17-5 ethanol WEL Long-term value: 1920	ma/m ³ , 1000 ppm	
64-17-5 ethanol WEL Long-term value: 1920	mg/m³, 1000 ppm	
64-17-5 ethanol WEL Long-term value: 1920 67-63-0 propan-2-ol WEL Short-term value: 1250) mg/m³, 500 ppm	
64-17-5 ethanol WEL Long-term value: 1920 67-63-0 propan-2-ol WEL Short-term value: 1250 Long-term value: 999 r	0 mg/m³, 500 ppm mg/m³, 400 ppm	
64-17-5 ethanol WEL Long-term value: 1920 67-63-0 propan-2-ol WEL Short-term value: 1250 Long-term value: 999 r 109-87-5 dimethoxymethan	0 mg/m³, 500 ppm mg/m³, 400 ppm ne	
64-17-5 ethanol WEL Long-term value: 1920 67-63-0 propan-2-ol WEL Short-term value: 1250 Long-term value: 999 r	0 mg/m ³ , 500 ppm mg/m ³ , 400 ppm ne 0 mg/m ³ , 1250 ppm	
64-17-5 ethanol WEL Long-term value: 1920 67-63-0 propan-2-ol WEL Short-term value: 1250 Long-term value: 999 r 109-87-5 dimethoxymethan WEL Short-term value: 3950 Long-term value: 3160 • DNELs	0 mg/m ³ , 500 ppm mg/m ³ , 400 ppm ne 0 mg/m ³ , 1250 ppm 0 mg/m ³ , 1000 ppm	
64-17-5 ethanol WEL Long-term value: 1920 67-63-0 propan-2-ol WEL Short-term value: 1250 Long-term value: 999 r 109-87-5 dimethoxymethan WEL Short-term value: 3950 Long-term value: 3160 • DNELs 68920-06-9 Naphtha (petrol	0 mg/m ³ , 500 ppm mg/m ³ , 400 ppm ne 0 mg/m ³ , 1250 ppm 0 mg/m ³ , 1000 ppm	
64-17-5 ethanol WEL Long-term value: 1920 67-63-0 propan-2-ol WEL Short-term value: 1250 Long-term value: 999 r 109-87-5 dimethoxymethan WEL Short-term value: 3950 Long-term value: 3160 • DNELs 68920-06-9 Naphtha (petrol Oral DNEL (Langzeit-w	0 mg/m ³ , 500 ppm mg/m ³ , 400 ppm ne 0 mg/m ³ , 1250 ppm 0 mg/m ³ , 1000 ppm leum), hydrotreated light viederholt) 699 mg/kg bw/day (BEV)	
64-17-5 ethanol WEL Long-term value: 1920 67-63-0 propan-2-ol WEL Short-term value: 1250 Long-term value: 999 r 109-87-5 dimethoxymethan WEL Short-term value: 3950 Long-term value: 3160 • DNELs 68920-06-9 Naphtha (petrol Oral DNEL (Langzeit-w	0 mg/m ³ , 500 ppm mg/m ³ , 400 ppm ne 0 mg/m ³ , 1250 ppm 0 mg/m ³ , 1000 ppm	

Printing date 29.07.2019

Trade name: Smooth Surface Cleaner

Version number 11

Revision: 29.07.2019

				(Contd. of pag
Inhalative	DNEL	(Langzeit-wiederholt)		
			608 mg/m³ Air (BEV)	
64742-48-	9 Nap	htha (petroleum), hyc	Irotreated heavy	
Oral	DNEL	(Langzeit-wiederholt)	125 mg/kg bw/day (BEV)	
Dermal	DNEL	. (Langzeit-wiederholt)	208 mg/kg bw/day (ARB)	
			125 mg/kg bw/day (BEV)	
Inhalative	DNEL	(Langzeit-wiederholt)	871 mg/m ³ Air (ARB)	
		(g,,	185 mg/m ³ Air (BEV)	
64-17-5 et	thanol			
Oral		(Langzeit-wiederholt)	87 mg/kg bw/day (BEV)	
Dermal		(Kurzzeit-akut)	950 mg/kg bw/day (BEV)	
	DNEL	(Langzeit-wiederholt)		
			206 mg/kg bw/day (BEV)	
Inhalative	DNEL	. (Kurzzeit-akut)	1,900 mg/m³ Air (ARB)	
			950 mg/m³ Air (BEV)	
	DNEL	. (Langzeit-wiederholt)	950 mg/m³ Air (ARB)	
			114 mg/m³ Air (BEV)	
67-63-0 pr	ropan-	2-ol		
Oral .	-	(Langzeit-wiederholt)	26 mg/kg bw/day (BEV)	
Dermal		(Langzeit-wiederholt)		
2 0		(g,,	319 mg/kg bw/day (BEV)	
Inhalativa		(Langzeit-wiederholt)	500 mg/m ³ Air (ARB)	
IIIIalative			89 mg/m ³ Air (BEV)	
			69 mg/m² Ali (BEV)	
<u>PNECs</u>				
64-17-5 et				
PNEC (wä	ássrig)	580 mg/l (KA)		
		0.79 mg/l (MW)		
		0.96 mg/l (SW)		
		2.75 mg/l (WAS)		
PNEC (fes	st)	0.63 mg/kg Trockenge	ew (BO)	
,	,	0.72 mg/kg Trockenge		
		2.9 mg/kg Trockengev		
		3.6 mg/kg Trockengev		
67-63-0 pr	ronan	•••	(600)	
•	•			
FINEC (Wa	assny)	2,251 mg/l (KA)		
		140.9 mg/l (MW)		
		140.9 mg/l (SW)		
140.9 mg/l (WAS)		• • •		
PNEC (fest) 28 mg/kg Trockengew		28 mg/kg Trockengew	и (ВО)	
552 mg/kg Trockengew 552 mg/kg Trockengew		552 mg/kg Trockenge	w (MWS)	
		552 mg/kg Trockenge	w (SWS)	
Additional	inform	ation: The	e lists valid during the making were used as basis.	
8.2 Expos				
		ve equipment:		
		ve and hygienic		
measures:		Kee	ep away from foodstuffs, beverages and feed.	
Immediately remove all soiled and contaminated clothing				
		Wa	sh hands before breaks and at the end of work.	
				(Contd. on page

according to 1907/2006/EC, Article 31

Printing date 29.07.2019 Version number 11 Revision: 29.07.2019 Trade name: Smooth Surface Cleaner (Contd. of page 5) Do not inhale gases / fumes / aerosols. Avoid contact with the skin. Avoid contact with the eves and skin. In case of brief exposure or low pollution use respiratory filter device. In case of Respiratory protection: intensive or longer exposure use self-contained respiratory protective device. Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation The selection of the suitable gloves does not only depend on the material, but · Material of gloves also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. · For the permanent contact gloves made of the following materials are Butyl rubber, BR suitable: Nitrile rubber, NBR · As protection from splashes gloves made of the following materials are suitable: Butoject (KCL, Art_No. 897, 898) Butyl rubber, BR Nitrile rubber, NBR · Not suitable are gloves made of the following materials: Strong material gloves Leather gloves · Eye protection: Tightly sealed goggles · Body protection: Use protective suit. **SECTION 9: Physical and chemical properties** · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid According to product specification Colour: · Odour: Specific type · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 42.3 °C · Flash point: -18 °C (Contd. on page 7)

GB

according to 1907/2006/EC, Article 31

Printing date 29.07.2019

Version number 11

Revision: 29.07.2019

Trade name: Smooth Surface Cleaner

	(Contd. of page 6)
· Flammability (solid, gas):	Not applicable.
Ignition temperature:	235 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits: Lower: Upper:	0.6 Vol % 19.9 Vol %
 Vapour pressure at 20 °C: 	440 hPa
 Density at 20 °C: Relative density Vapour density Evaporation rate 	0.76 g/cm ³ Not determined. Not determined. Not applicable.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
 <u>Viscosity:</u> <u>Dynamic:</u> <u>Kinematic:</u> 	Not determined. Not determined.
Solvent content: Organic solvents: 9.2 Other information	100.0 % No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
 10.2 Chemical stability 	
 Thermal decomposition / 	
conditions to be avoided:	No decomposition if used according to specifications.
 10.3 Possibility of hazardous 	
reactions	No dangerous reactions known.
 10.4 Conditions to avoid 	No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition	
products:	No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:			
68920-06-	68920-06-9 Naphtha (petroleum), hydrotreated light		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>2,800 mg/kg (rabbit)	
	LD50	>2,000 mg/kg (rat)	
Inhalative	LC50/4 h	>23.3 mg/l (rat)	
64742-48-	64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5,000 mg/kg (rat)	
			(Contd. on page 8)

- GB

Printing date 29.07.2019

Version number 11

Revision: 29.07.2019

Trade name: Smooth Surface Cleaner

		(Contd. of page 7)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
	LD50	>5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>4,951 mg/l (rat)	
64-17-5 et	hanol		
Oral	LD50	10,470 mg/kg (rat) (OECD 401)	
	NOAEL-Werte	>3,000 mg/kg (rat) (OECD 451)	
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50/4h	20,000 mg/m3 (rat)	
	LC50/4 h	120 mg/l (rat) (OECD 403)	
	LC50/48h	5,012 mg/l (ceriodaphnia Dubai)	
		12,340 mg/l (daphnia magna)	
		8,150 mg/l (Leuciscus idus)	
67-63-0 pi	opan-2-ol		
Oral	LD50	>2,000 mg/kg (rabbit)	
		5,840 mg/kg (rat) (OECD 401)	
	NOAEL-Werte	400 mg/kg (rat)	
Dermal	LD50	13,900 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50/8h	47.5 ppm (rat)	
	LC50/4 h	30-46.5 mg/l (rat)	
	LC50	25,000 mg/m3 (rat)	
	LC50/48h	>100 mg/l (Leuciscus idus)	
	itant effect:		
	sion/irritation	Based on available data, the classification criteria are not met.	
	<u>ve damage/irrita</u> v or skin sensiti		
		ty, mutagenicity and toxicity for reproduction)	
	mutagenicity	Based on available data, the classification criteria are not met.	
Carcinoge		Based on available data, the classification criteria are not met.	
<u>Reproduct</u>		Based on available data, the classification criteria are not met.	
	gle exposure	May cause drowsiness or dizziness. Based on available data, the classification criteria are not met.	
	STOT-repeated exposure Aspiration hazard Based on available data, the classification criteria are not met. May be fatal if swallowed and enters airways.		
.			

SECTION 12: Ecological information

· 12.1 Toxicity

 Aquatic toxic 	<u>Aquatic toxicity:</u>			
68920-06-9	68920-06-9 Naphtha (petroleum), hydrotreated light			
EC50/48h	3 mg/l (daphnia magna)			
EL50/72h	10-30 mg/l (Pseudokirchneriella subcapitata)			
LL50/96h	>13.4 mg/l (Oncorhynchus mykiss)			
NOELR/72h	10 mg/l (Pseudokirchneriella subcapitata)			
NOEC/21d	0.17 mg/l (daphnia magna)			
LC50/96h	<10 mg/l (daphnia magna)			
64742-48-9 Naphtha (petroleum), hydrotreated heavy				
EL0/48h	1,000 mg/l (daphnia magna)			
EL50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)			
LL50/96h	>1,000 mg/l (Oncorhynchus mykiss)			
NOELR/72h	100 mg/l (Pseudokirchneriella subcapitata)			
	(Contd. on page 9)			

Printing date 29.07.2019

Version number 11

Revision: 29.07.2019

Trade name: Smooth Surface Cleaner

64-17-5 etha	nol	(Contd. of page 8)
 LC50/24h	11,200 mg/l (Salmo g	nairdheri)
EC50/48h	9,268-14,221 mg/l (d	<i>,</i> ,
2000/4011		strum capricornutum) (OECD 201)
EC0	6,500 mg/l (pseudom	
200	5,000 mg/l (scenede	
EC10	11.5 mg/l (CHV)	sinus quauncauda)
EC50/72h	275 mg/l (CHV) (OE(201)
LC50/96h		ynchus mykiss) (OECD 203)
2030/3011	15,300 mg/l (pimeph	
 67-63-0 prop		
 EC50/24h	9,714 mg/l (daphnia	magna)
EC50/2411	>1,000 mg/l (BES)	magna)
LC50/24h	9,714 mg/l (daphnia	magna)
	22,000 mg/l (Photoba	
IC50/72h		desmus subspicatus)
EC10/18h		nonas putida) (DIN 38412)
EC50/48h	13,299 mg/l (daphnia	
EC50/72h	>1,000 mg/l (green a	o ,
2000/7211	>100 mg/l (Scenedes	
LC50/96h	6,550 mg/l (piscis)	sinus subspicatus)
2030/3011	9,640 mg/l (Pimepha	les prometes)
· 12.2 Persist	• • •	
degradabilit		No further relevant information available.
· 12.3 Bioaccumulative potential		No further relevant information available.
12.4 Mobility		No further relevant information available.
 Ecotoxical ef Remark: 	tects:	Toxic for fish
	ological information:	
· General note		Also poisonous for fish and plankton in water bodies.
		Toxic for aquatic organisms
		Danger to drinking water if even extremely small quantities leak into the ground.
		Do not allow product to reach ground water, water course or sewage system. Water hazard class 2 (German Regulation) (Self-assessment): hazardous for
		water
	of PBT and vPvB as	
• <u>PBT:</u>		Not applicable.
· <u>vPvB:</u> · 12 6 Other a	dverse effects	Not applicable. No further relevant information available.
 <u></u>		
SECTION 13	: Disposal considera	ations
	-	
	ation	Must not be disposed together with household garbage. Do not allow product to
· Recommendation		reach sewage system.
. Uncleaned a	ackading:	
 Uncleaned p Recommend 		Disposal must be made according to official regulations.
		(Contd. on page 10)

Printing date 29.07.2019

Version number 11

Revision: 29.07.2019

	(Contd. of
SECTION 14: Transport information	
14.1 UN-Number	
ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S., special provision (METHYLAL, ISOPROPANOL (ISOPROPYL ALCOH ENVIRONMENTALLY HAZARDOUS
IMDG	FLAMMABLE LIQUID, N.O.S. (METHYLAL, ISOPROP, (ISOPROPYL ALCOHOL)), MARINE POLLUTANT
ΙΑΤΑ	FLAMMABLE LIQUID, N.O.S. (METHYLAL, ISOPROPA (ISOPROPYL ALCOHOL))
14.3 Transport hazard class(es)	
ADR	
<u>Class</u> Label	3 (F1) Flammable liquids. 3
IMDG	
Class	3 Flammable liquids.
	3
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	Product contains environmentally hazardous substances:
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (lish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number: Stowage Category	F-E, <u>S-E</u> B
14.7 Transport in bulk according to Ann Marpol and the IBC Code	nex II of
	Not applicable.
Transport/Additional information:	
ADR	

(Contd. on page 11)

according to 1907/2006/EC, Article 31

Printing date 29.07.2019

Version number 11

Revision: 29.07.2019

Trade name: Smooth Surface Cleaner

(Contd. of page 10)
Code: E2 Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
Z D/E
1L Code: E2
Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIAL PROVISION 640D (METHYLAL, ISOPROPANOL (ISOPROPYL ALCOHOL)), 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

Named dangerous substances -	
ANNEX I	None of the ingredients is listed.
Seveso category	E2 Hazardous to the Aquatic Environment
	P5c FLAMMABLE LIQUIDS
Qualifying quantity (tonnes) for the	
application of lower-tier	
requirements	200 t
· Qualifying quantity (tonnes) for the	
application of upper-tier	
requirements	500 t
REGULATION (EC) No 1907/2006	
ANNEX XVII	Conditions of restriction: 3
National regulations:	
¥	Freedow and the other than a second sector of the sector o
Information about limitation of use:	Employment restrictions concerning juveniles must be observed.
· Waterhazard class:	Water hazard class 2 (Self-assessment): hazardous for water.
VOC EU	762.0 g/l
15.2 Chemical safety	v
assessment:	A Chemical Safety Assessment has not been carried out.
	•

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

<u>Relevant phrases</u>	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
<u>Department issuing SDS:</u> <u>Contact:</u>	Laboratory Dieter Zimmermann Elke Hake
 Abbreviations and acronyms: 	Fon ++49 (0)911 64296-59 @mail E.Hake@akemi.de ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods (Contd. on page 12)

Printing date 29.07.2019

Version number 11

Revision: 29.07.2019

Trade name: Smooth Surface Cleaner

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances	(Contd. of page 11)
CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)	
PNEC: Predicted No-Effect Concentration (REACH)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic ha	zard – Category 2 GB –