

Stone Polish - silicone based

Technical Data Sheet

Page 1 of 1

Properties:

AKEMI® Stone Polish is a care product made of reactive silicone oils with lubricants and polishing agents. The product reacts with air humidity and thus develops a resistant surface protection. It is resistant to weathering and yellowing, allows the surface to breathe and is therefore very well suited for outdoor use. AKEMI® Stone Polish renders the stone surface stain-resistant and easier to care. The polishing agents contained allow removal of minor scratches in lacquer coatings and adhesive dirt also on sensitive surfaces. The product is harmless to health upon contact with food products after hardening, certified by an external German testing institute.

Application Area:

AKEMI® Stone Polish is suited to the care of closed natural and artificial stone surfaces with high gloss, s.a. marble, granite, slabs from Solnhofen, quartzite and terrazzo as well as metal and synthetic materials used indoor and, as no waxes are contained, especially outdoor. AKEMI® Stone Polish is an ideal supplementary product for the periodic care and improved protection of table tops and kitchen countertops which have been impregnated with AKEMI® Stain Repellent products.

Instructions for Use:

- 1. Clean surfaces thoroughly with AKEMI® Stone Cleaner and allow them to dry.
- 2. Shake before use.
- 3. Apply a thin layer with a soft cloth.
- 4. Allow to dry, then polish with a soft cloth or polishing wool.
- 5. For regular cleaning AKEMI® Crystal Clean or AKEMI® Mild Stone Soap is very well suited.
- 6. Sufficient ventilation (approx. 2 3 days) is necessary when using the product in food areas.

Special Notes:

- The product is only suited for polished or smooth surfaces.
- A slight colour enhancement may be possible.
- No slip resistance on floorings.
- For proper waste disposal, the container must be completely emptied.
- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.

Technical Data: Coverage: approx. 20 - 30 m²/liter

Colour: milky white

Density: approx. 0.78 g/cm³

Storage: If stored in dry and cool condition (5-25°C/41-77°F) in its closed original

container at least 24 months from production.

Health & Safety: Read Safety Data Sheet before handling or using this product.

Important Notice: The above information is based on the latest stage of development and

application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample

piece.

TDS 01.22