

TIGERCUT 200 VARIO MET WATERTOEOVOER



Data sheet

TIGERCUT 200 Vario

Wet stone cutter



Guide Nibs
to position along the cutting line (on the front and back edges of the safety cover).



Adjustable cover positioning for horizontal ...



or vertical cutting



Quick fastening on adjustable safety cover.



Autobalancer
The autobalancer consists of steel balls, lubricated in oil, that freely move around the drive shaft in a housing similar to that for ball bearings, and so perfectly level out any imbalance.

Brief description:

Professional freehand wet cutter for a wide range of uses. Compact design with large cutting depth of maximum 6.3 cm.

Special features:

- Powerful one-hand grinder - constant speed control with lots of power reserves for continuous running.
- Adjustable cover positioning for horizontal and vertical cuts.
- Precise positioning and cutting using the guide nibs.
- Very thin safety cover enables a good view to the cut.
- Ergotec anti-vibration handle.
- Hose spacer ensures distance to the handle. Hose routing to behind the machine.
- Proven, flexible and transparent splash guard. This means that less moisture and dirt is sucked into the engine compartment. This significantly increases the service life of the machine.
- 2 service ports for easy replacements of the carbon brushes.
- Spindle lock for easy tool changes.
- Soft start and electronics for constant speed even under load.
- Temperature-dependent overload protection.
- Speed range designed for stone cutting with infinitely variable speed regulation.
- Wear-resistant and unbreakable silicone power cable in signal colour (clearly visible).
- Special requests (e.g. for longer connecting cables or hoses) can be considered.
- Repair service for all of our machines.

Application:

Dry stone cutter for natural or artificial stone processing. Especially suitable for stonemasons, sculptors, restorers, tilers, renovators, floor renovators, etc.

Technical Data:

Voltage:	230/115 Volt	Spindle thread:	M 14 / 22.2 mm
Power:	1,750 Watt	Weight:	3.5 kg
Speed:	1,700 - 6,800 rpm	Soft start,	
Tool Ø max.:	200 mm	Overload protection	
Cutting depth max.	63 mm		

Included:

Silicone connecting cable 4 m, personal protection switch PRCD or CEE-plug, bail handle, hose connector with Velcro fastening, hose 2.5 m, guard with water supply, bayonet lock, water feeding, splash guard, twin hole wrench, autobalancer, case.

Available versions:

TIGERCUT 200 Vario DI	230V	(with PRCD)	Item no.: 003.036.201
TIGERCUT 200 Vario CEE	230V	(for transformer)	Item no.: 003.036.204
TIGERCUT 200 Vario DI	115V	(with PRCD)	Item no.: 003.036.203
TIGERCUT 200 Vario CEE	115V	(for transformer)	Item no.: 003.036.205