

## Gravity

### EXTRA CLEAR SOLID VINYLESTER GLUE

Extra strong and ultra fast extra clear glue characterized by resistance to freeze and heat and excellent colour stability. Multi-material, it is ideal for visible bonding and lamination.



 **EXTREME AND ULTRA FAST BONDING**

 **STABLE TO SUNLIGHT**

 **RESISTANT TO HEAT AND LOW TEMPERATURES**

#### Technical data:

- ◆ **Density at 25°C gr/cm³:** 1.1
- ◆ **Standard colour:** transparent
- ◆ **Appearance:** extra clear paste

#### Approximate consumption:

- ◆ **For grouting:**  
20-30 linear meters
- ◆ **For bonding:**  
30-40 mt<sup>2</sup>

The stated duration is only approximate



Indoor  
Outdoor



Freeze & Heat



Natural stone



Quartz



Ceramic

#### How to apply it:

- ◆ Remove the desired quantity of product from the container and weigh it.
- ◆ Comply with the ratio between the product and its hardener as indicated in the TDS.
- ◆ Use clean tools when mixing.
- ◆ If necessary, add liquid or pigment dyes before mixing with the hardener.
- ◆ Make sure that the material on which the product will be applied is clean and dry.
- ◆ To clean tools soiled with mastics, use non-greasy solvents, e.g. Acetone or Butyl Acetate. Use the necessary PPE.
- ◆ Read the technical and safety data sheet carefully.
- ◆ Close the containers with their original caps for correct storage.
- ◆ Avoid prolonged contact with air.

#### Performance:

<b>Adhesion strength [Mpa]</b>	ceramic 13.0
<b>Gel time in mass at 25°C</b>	3.30-4.30 min
<b>Workability time at 25°C</b>	25-40 min
<b>Extraclear</b>	yes
<b>Stability to sunlight</b>	excellent
<b>Wet effect</b>	superb
<b>Spreadability</b>	excellent
<b>Adhesion on wet</b>	no

#### Safety measures:

Before use, please read the instructions in the safety data sheet and the notes on the packaging. Close the container after use. For professional use only.

#### Warnings:

When a surface is treated for the first time, it is advisable to evaluate its effect or adhesion on a sample or hidden corner.



Opening the jar



Spatula product



Addition of hardener



Post mix verticality



Mixed product appearance



Hardened product appearance