

Eliox A+B

SOLID EPOXY MASTIC

Extra strong and extra clear solid glue characterized by the total absence of yellowing in the sun over time. Completely invisible, easily polished and suitable for extreme temperatures, it is ideal for all visible bonding.



EXTRA STRONG BONDING



EXTRA CLEAR



IDEAL FOR VISIBLE BONDING

Technical data:

- ◆ **Density at 25°C gr/cm³:** 1.2 / 1.1
- ◆ **Standard colour:** clear
- ◆ **Appearance:** extra clear

Approximate consumption:

- ◆ **For grouting:**
20-30 linear meters
- ◆ **For bonding:**
30-40 mt2

The stated duration is only approximate

Indoor
Outdoor

For food contact



Natural stone



Quartz



Ceramic

How to apply it:

- ◆ Remove the desired quantity of product from the container and weigh it.
- ◆ Comply with the ratio between part A and part B as indicated in the TDS.
- ◆ Use clean tools when mixing.
- ◆ If necessary, add liquid or pigment dyes before mixing with the hardener.
- ◆ Make sure that the material on which the product will be applied is clean and dry.
- ◆ To clean tools soiled with mastics, use non-greasy solvents, e.g. Acetone or Butyl Acetate. Use the necessary PPE.
- ◆ Read the technical and safety data sheet carefully.
- ◆ Close the containers with their original caps for correct storage.
- ◆ Avoid prolonged contact with air.

Performance:

Adhesion strength [Mpa]	ceramic 17
Gel time in mass at 25°C	10-15 min
Workability time at 25°C	24 h
Extraclear	yes
Stability to sunlight	excellent
Wet effect	low
Spreadability	excellent
Adhesion on wet	no

Safety measures:

Before use, please read the instructions in the safety data sheet and the notes on the packaging. Close the container after use. For professional use only.

Warnings:

When a surface is treated for the first time, it is advisable to evaluate its effect or adhesion on a sample or hidden corner.



Part A



Part B



Mixing



Post mix verticality



Mixed product appearance



Hardened product appearance