## Tenax

### Si Silicone

#### **NEUTRAL SEALANT**

Neutral multi-material silicone sealant ideal for materials that are easy to halation. Elastically seals and fixes ensuring a watertight and waterproof seal and long-lasting sealing.





PERFECT SEALING



**QUICK GRIP** 



 $\overset{\leftarrow}{+}$  no halos

#### **Technical data:**

Appearance: transparent or coloured paste

#### **Indicative consumption:**

- For grouting: 20-30MT linear
- ◆ For bonding: 30-40MT2

The stated consumption is merely indicative









#### How to apply it:

- The surfaces to be sealed must be dry and free of dust, oil, rust or other contaminants.
- Delimit the joint with adhesive tape.
- Cut off the upper portion of the cartridge above the thread.
- Cut the spout to the desired diameter and screw it onto the cartridge.
- Extrude the product.
- Perfect the seal within 5 min and remove any excess with a cutter.
- Please read the technical data sheet carefully for proper use.

#### **Performance:**

Skin formation time at 23°C/45%r.h:

15-30min

Wide range of colours

yes

#### **Safety measures:**

Read the instructions in the technical and safety data sheet and the notes on the packaging before use. Close the container after use. For professional use only.

#### **Warnings:**

When a surface is treated for the first time, it is advisable to evaluate the effect or adhesion on a sample or hidden corner.

# Tenax



**Thread cutting** 



**Spout insertion** 



**Product extrusion** 



**Joint** 



**Bonding the material** 

Final result