

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: COMPONENT BONDER.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: INTEGRA Adhesives
Unit 22, Bentall Business Park
Glover Road
Washington
Tyne & Wear
NE37 3JD
UK

Tel: +44(0)191 419 6444

Fax: +44(0)191 419 6445

Email: sds-europe@ipscorp.com

1.4. Emergency telephone number

Emergency tel: CHEMTEL Tel: 001 813-248-0573 (International)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Eye Dam. 1: H318; Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1A: H317; STOT SE 3: H335

Most important adverse effects: Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H335: May cause respiratory irritation.
H412: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

COMPONENT BONDER.

Page: 2

Hazard pictograms: GHS02: Flame
GHS05: Corrosion
GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261: Avoid breathing vapours.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

METHYL METHACRYLATE - REACH registered number(s): 01-2119452498-28-0000, 01-2119452498-28-0025, 01-2119452498-28-0028

EINECS	CAS	PBT / WEL	CLP Classification	Percent
201-297-1	80-62-6	-	Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317	50-70%

URETHANE METHACRYLATE OLIGOMER - REACH registered number(s): EXEMPT

934-766-0	-	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-10%
-----------	---	---	---	-------

2-METHYLPROPENOIC ACID - REACH registered number(s): 0000-211-9463884-26-0000

201-204-4	79-41-4	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1A: H314	1-10%
-----------	---------	---	--	-------

[cont...]

SAFETY DATA SHEET

COMPONENT BONDER.

Page: 3

3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE

252-091-3	34562-31-7	-	Acute Tox. 4: H302+H312; Aquatic Chronic 4: H413; Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-10%
-----------	------------	---	---	-------

P TOLUENE SULPHONYL CHLORIDE

202-684-8	98-59-9	-	Met. Corr. 1: H290; Skin Irrit. 2: H315; Eye Dam. 1: H318; Skin Sens. 1A: H317	1-10%
-----------	---------	---	--	-------

2,6-DI-TERT-BUTYL-P-CRESOL - REACH registered number(s): 01-2119565113-46-XXXX

204-881-4	128-37-0	-	Aquatic Acute 1: H400; Aquatic Chronic 1: H410	<1%
-----------	----------	---	--	-----

CUMENE HYDROPEROXIDE

201-254-7	80-15-9	-	Org. Perox. EF: H242; Acute Tox. 3: H331; Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Skin Corr. 1B: H314; Aquatic Chronic 2: H411	<1%
-----------	---------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

[cont...]

SAFETY DATA SHEET

COMPONENT BONDER.

Page: 4

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Wear protective clothing for prolonged exposure/high concentration Wash hands after use.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC1: Adhesives, sealants.

Section 8: Exposure controls/personal protection

[cont...]

SAFETY DATA SHEET

COMPONENT BONDER.

Page: 5

8.1. Control parameters

Hazardous ingredients:

METHYL METHACRYLATE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	203mg/m3	416mg/m3	-	-

2-METHYLPROPENOIC ACID

UK	72 mg/m3	143 mg/m3	-	-
----	----------	-----------	---	---

P TOLUENE SULPHONYL CHLORIDE

UK	-	5mg/m3	-	-
----	---	--------	---	---

2,6-DI-TERT-BUTYL-P-CRESOL

UK	10 mg/m3	-	-	-
----	----------	---	---	---

DNEL/PNEC Values

Hazardous ingredients:

METHYL METHACRYLATE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	210mg/m3	Workers	Systemic
DNEL	Dermal	74.3 mg/m3	Workers	Systemic
PNEC	Water	0.94 mg/l	-	-

2-METHYLPROPENOIC ACID

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	88mg/m3	Workers	Local
DNEL	Dermal	4.25mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	29.6mg/m3	Workers	Systemic
DNEL	-	360mg/m3 100ppm	Workers	Short term
PNEC	Fresh water	0.82mg/l	Workers	-
PNEC	Marine water	0.82mg/l	Workers	-
PNEC	Sewage treatment plant (STP)	10mg/l	Workers	-
PNEC	Soil (agricultural)	1.2mg/kg	Workers	-

2,6-DI-TERT-BUTYL-P-CRESOL

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	3.5	Workers	Systemic

[cont...]

SAFETY DATA SHEET

COMPONENT BONDER.

Page: 6

CUMENE HYDROPEROXIDE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	6 mg/m3	Workers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Avoid release to the environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Amber

Odour: Characteristic odour

Evaporation rate: 3.1 (relative)*

Solubility in water: 15.3 g/l (20°C)

Also soluble in: Most organic solvents.

Viscosity: Highly viscous

Boiling point/range°C: 100.3

Melting point/range°C: -48

Flammability limits %: lower: 2.1

upper: 12.5

Flash point°C: 15

Part.coeff. n-octanol/water: 1.38

Autoflammability°C: 435

Vapour pressure: 37hPA (20°C)

Relative density: 0.97

pH: Not applicable.

9.2. Other information

Other information: *Flammability based on data for methyl methacrylate

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

SAFETY DATA SHEET

COMPONENT BONDER.

Page: 7

10.4. Conditions to avoid

Conditions to avoid: Avoid extreme temperatures, open flames, sparks, and direct sunlight. Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

METHYL METHACRYLATE

DERMAL	RBT	LD50	>5000	mg/kg
INHALATION	RAT	4H LC50	29.8	mg/l
ORAL	RAT	LD50	>5000	mg/kg

2-METHYLPROPENOIC ACID

DERMAL	RBT	LD50	500-1000	mg/kg
ORAL	RAT	LD50	1320	mg/kg
VAPOURS	RAT	1H LC50	7.1	mg/l

3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE

DERMAL	RBT	LD50	>1000	mg/kg
ORAL	RAT	LD50	>500	mg/kg

P TOLUENE SULPHONYL CHLORIDE

ORAL	RAT	LD50	4680	mg/kg
------	-----	------	------	-------

2,6-DI-TERT-BUTYL-P-CRESOL

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2930	mg/kg

CUMENE HYDROPEROXIDE

ORL	MUS	LDLO	5	gm/kg
ORL	RAT	LD50	382	mg/kg
SCU	RAT	LD50	382	mg/kg

[cont...]

SAFETY DATA SHEET

COMPONENT BONDER.

Page: 8

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	-	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

METHYL METHACRYLATE

DAPHNIA MAGNA	48H EC50	69	mg/l
GREEN ALGA (<i>Selenastrum capricornutum</i>)	72H EC50	>110	mg/l
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	>79	mg/l

2-METHYLPROPENOIC ACID

Daphnia magna	48H EC50	>130	mg/l
GREEN ALGA (<i>Selenastrum capricornutum</i>)	96H ErC50	45	mg/l
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	85	mg/l

P TOLUENE SULPHONYL CHLORIDE

Daphnia magna	48H EC50	70	mg/l
FISH	96H LC50	>100	mg/l
GREEN ALGA (<i>Selenastrum capricornutum</i>)	72H ErC50	>100	mg/l
ZEBRAFISH (<i>Brachydanio rerio</i>)	96H LC50	>100	mg/l

[cont...]

SAFETY DATA SHEET

COMPONENT BONDER.

Page: 9

2,6-DI-TERT-BUTYL-P-CRESOL

ALGAE	72H ErC50	0.758	mg/l
Aquatic invertebrates	48H EC50	0.48	mg/l
FISH	96H LC50	0.199	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: NB: the users attention is drawn to the possible existence of regional or national regulations regarding disposal.

Waste code number: 08 04 09

Disposal of packaging: According to local regulations. Emptied container might retain product residues. Follow all warnings even after the container is emptied. waste adhesives and sealants containing organic solvents or other hazardous substances

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

14.3. Transport hazard class(es)

Transport class: 3

[cont...]

SAFETY DATA SHEET

COMPONENT BONDER.

Page: 10

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.
H242: Heating may cause a fire.
H290: May be corrosive to metals.
H302: Harmful if swallowed.
H302+H312: Harmful if swallowed or in contact with skin
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H331: Toxic if inhaled.
H335: May cause respiratory irritation.
H373: May cause damage to organs through prolonged or repeated exposure.
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.
H413: May cause long lasting harmful effects to aquatic life.

Legal disclaimer: This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]