

Liquido trasparente

TRANSPARENT LIQUID POLYESTER MASTIC

Transparent liquid mastic with high adhesion. Its reactivity even at low temperatures, rapid hardening and easy penetration make it the ideal product for those looking for a clear liquid mastic to repair imperfections, fill and bond even at low temperatures.



 **STRONG AND FAST BONDING**

 **REACTIVE EVEN AT LOW TEMPERATURES**

 **EASILY PENETRATES IMPERFECTIONS**

Technical data:

- ◆ **Density at 25°C gr/cm³:** 1.1
- ◆ **Standard colour:** transparent
- ◆ **Appearance:** yellowish liquid

Approximate consumption:

- ◆ **For grouting:**
23-30 linear meters

The stated duration is only approximate



How to apply it:

- ◆ Remove the desired quantity of product from the container and weigh it.
- ◆ Comply with the ratio between the product and its hardener as indicated in the TDS.
- ◆ Use clean tools when mixing.
- ◆ If necessary, add liquid or pigment dyes before mixing with the hardener.
- ◆ Make sure that the material on which the product will be applied is clean and dry.
- ◆ To clean tools soiled with mastics, use non-greasy solvents, e.g. Acetone or Butyl Acetate. Use the necessary PPE.
- ◆ Read the technical and safety data sheet carefully.
- ◆ Close the containers with their original caps for correct storage.
- ◆ Avoid prolonged contact with air.

Performance:

Adhesion strength [Mpa]	marble 9.0
Gel time in mass at 25°C	5-8 min
Workability time at 25°C	60-80 min
Extraclear	no
Stability to sunlight	good
Wet effect	superb
Spreadability	n.a.
Adhesion on wet	no

Safety measures:

Before use, please read the instructions in the safety data sheet and the notes on the packaging. Close the container after use. For professional use only.

Warnings:

When a surface is treated for the first time, it is advisable to evaluate its effect or adhesion on a sample or hidden corner.