

COLOUR-ENHANCER SEALER, WET EFFECT



Enhances and revitalizes the colour and the natural grain of the material, it also protects from the absorption of staining oily, colourful and aqueous substances. It also gives an anti-graffiti protection.



SOLVENT BASE



ENHANCER



ANTI-GRAFFITI

TECHNICAL CHARACTERISTICS

Solvent based product of depth that protects and enhances the natural grain of the material.

HOW TO APPLY IT

Tools



Applied by paintbrush, with a cloth or sponge or a fleece.

Mode

To be applied pure on completely dry and clean surfaces, using a paintbrush, cloth, sponge. For best results, on most absorbent surfaces, apply wet on wet, making sure to apply the amount that the material naturally absorbs evenly, avoiding the direct sunlight and the temperature of the material above 30 degrees. If applied in excess, a sticky surface film is created. After a few seconds after application, remove the product in excess not absorbed, with a clean cloth or sponge. Desired protection is reached 24 hours after treatment. After application, do not step on the surface, for 4-6 hours.

WHERE TO APPLY IT

- MARBLE**
- GRANITE**
- NATURAL STONES**
limestone, travertine, rosso verona, sandstone
- AGGLOMERATE**



PLUS/ADVANTAGES

- IT GIVES TONE AND BEAUTY TO MATERIALS
- ANTI-STAIN; PROTECTS AGAINST ATMOSPHERIC AGENTS
- DOES NOT YELLOW
- IT IS UV RESISTANT
- ANTI-GRAFFITI


TECHNICAL DATA

Density at 25 °C gr/cm ³	0.95
Appearance	opalescent liquid
Colour	colourless

COVERAGE

The consumption depends greatly on the porosity of the material

1L of product	
HONED STONE AND MARBLE	20-35 m ² 215-376 sq.ft.
POLISHED MARBLE AND GRANITE	30-50 m ² 323-538 sq.ft.



UNTREATED



TREATED

PACKAGING

0,25-1-5-10-20-200 litres.

HOW TO STORE IT

Under normal conditions of use and work, the product stored properly away from heat, moisture and direct sunlight is guaranteed 24 months. Close carefully the packaging after use.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. If the surface is treated for the first time, we recommend that you assess the effect and the adherence of the material on a sample or hidden corner.

LEGISLATION

Before use please read the instructions on the safety data sheet and the following notes on the cans.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



Scans to access multimedia contributions